

**Available Heights**

Pressed  
Spear  
Point Top



48in (4ft)



54in (4.5ft)  
Flush Bottom



60in (5ft)



72in (6ft)  
4 Rails



**Available Widths**




36in (3ft)



48in (4ft)



60in (5ft)



72in (6ft)

**Available Picket Spacing**



Standard  
3-13/16in Gap




Double  
1-5/8in Gap

**Available Top Designs**




Flat Top



Arch Top

**Available Hardware Options**



Standard Hardware  
(2) Self-Closing Aluminum  
Hinges & (1) Gravity Latch



Pool Code Hardware  
(2) Self-Closing Tru-Close  
Hinges & (1) MagnaLatch

**Available Colors**



Black

**ICC Swimming Pool Code Approved Heights**

**Standard Picket Spacing**

54in Flush Bottom, 60in, 72in

**Double Picket Spacing**

48in, 54in, 60in, 72in

**Pool Code Gate Hardware Required.**

**Check local codes before purchasing.**



**Gate Specifications**

**Material:** 6063-T5 Aluminum

**Coating:** AAMA 2604 Approved Polyester Powder Coat

**Pickets:** 5/8in Sq. x 0.050in Wall **Rails:** 1in Sq. x 0.055in Wall

**Uprights:** 1-1/2in Sq. x 0.100in Wall

**All welded construction.**